

## Declaration of performance according to Regulation (EU) 305/2011 Nr. 23638-CPR-2015/05/13

1. Unique identification code of product type: Nevado Aqua Compact 23/638

... Singus identification code of product type, Nevado Aqua compact 25/050

buildings

3. Manufacturer: Olsberg GmbH

Tel: +49 (0) 2962 / 805 – 0

Hüttenstraße 38 59939 Olsberg Fax: +49 (0) 2962 / 805 – 180 e-mail: kaminofen@olsberg.com

Roomheaters fired by solid fuel (intermittent burning), Roomheating in

4. Authorized: ---

2. Application:

5. System(s) for assessment and verification of constancy of performance of the construction product: System 3

The notified test laboratory has carried out the initial testing according to system 3.
Notified body/bodies: Feuerstättenprüfstelle Kahl GmbH, NB 2289, D 44577 Castrop-Rauxel

7. Declared performance:

Harmonised technical specifications	EN 13240:2001/A2:2004/AC:2007
Key features	Performance
Fire safety	passed
- Fire resistance/reaction to fire	A1
- Safety distance to combustible materials	Minimum distance in mm
	Rear: 100, Sides: 100, Front: 800
	(stove's radiation area, measured from the combustion
	chamber's inspection glass), Floor: 0
- Risk of burning fuel falling out	passed
Cleanability	passed
Emission of combustion products	
- CO	Logs: 0,07% / Wood briquette: 0,09% / Brown coal
O. fara to the same to	briquette: 0,09%
Surface temperature	passed
Electrical safety	not applicable
Release of dangerous substances	npd
Max. operating pressure	2,5 bar
Flue gas temperature	
- in test section	Logs: 229°C / Wood briquette: 220°C / Brown coal briquette: 222°C
- at connecting piece at nominal heat output	Logs: 260°C / Wood briquette: 242°C / Brown coal
	briquette: 249°C
Mechanical strength	npd
(for the installation of a chimney)	
Heat output / energy efficiency	passed
- Nominal heat output	8,0 kW
- Room heating capacity	2,8 kW
- Water heating capacity	5,2 kW
Efficiency	Logs: 80,27% / Wood briquette: 79,22% / Brown coal briquette: 78,91%
Durability	npd

8. The performance of the above mentioned product corresponds to the declared performance in (7). Basis of the declared performance is the test report FK 40 12 135.

The manufacturer (3) is solely responsible for the preparation of this declaration

Signed for and on behalf of the manufacturer:

Dr. Volker Schulte, Authorised signatory, management

Olsberg GmbH Hüttenstraße 38

olsberg

59939 Olsberg

Olsberg, 22/09/2020